



## Watts® Reverse Osmosis Systems with Kwik-Change™ Cartridges and Membranes.

*Systems are designed for consumers who demand the "best", and appeal to marketing professionals and water quality dealers who prefer to offer their customers top quality equipment, with "cutting-edge" advantages over competitive products.*

*Unlike conventional reverse osmosis systems, Watts drinking water systems with Kwik-Change cartridges have no sumps, so their proprietary filter elements and membranes are easy to replace. This appeals to consumers because of convenience, and to dealers who service drinking water systems.*

*Full product line is available, including:*

- 50 GPD models
- 100 GPD models
- Metal tanks
- Plastic tanks
- Top mount faucets
- Standard faucets
- Models for coolers
- Custom systems
- Drinking water systems with filter elements and hollow fiber membranes.



### Features & benefits

- Cartridges are connected and removed with a simple 1/4 turn.
- No filter sumps!
- No fuss!
- No mess!
- Automatic shut-off when cartridges are removed.
- Tank and faucet options are available.
- Valves are built into the heads to prevent back-flow for water quality assurance.
- WQA Gold Seal Certified to NSF/ANSI Std. 58.



WQA Gold Seal  
Certified to  
NSF / ANSI  
Std. 58

### Models

Model Number	Gallons Per Day	Faucet	Tank
WQC4RO11-50PT	50	Chrome*	Plastic
WQC4RO11-50MT	50	Chrome*	Metal
WQC4RO11-50MTLR	50	Chrome	Metal
WQC4RO13-100PT	100	Chrome*	Plastic
WQC4RO13-100MT	100	Chrome*	Metal
WQC4RO13100MTLR	100	Chrome	Metal

Note: Capacity based on 60 psi and 77°F. \*Top mount premium faucet.

### Specifications

Operating pressure (PSI)	40 (min.) to 100 (max.)
Dimensions (50 GPD)	12" x 12" x 3"
Dimensions (100 GPD)	14" x 12" x 3"
Typical TDS rejection rates	98%



## Conventional RO systems

Conventional RO systems may provide high quality water. However, cartridges and membranes are difficult to replace because they are installed in housings and must be removed. This procedure includes the need to shut off and drain down the system; open the housings with a wrench; remove cartridges; empty water from the sumps; clean the filter and membrane housings; replace cartridges; re-pressurize; and check for leaks.

Because conventional systems are difficult to service, routine maintenance may be delayed. Therefore, consumers may not get the quality water they desire, unless a qualified dealer is called to service their system.

***Watts® Kwik-Change RO systems are so easy to service you'll get great quality water every time!***

Hinge bracket for easy handling.

Automatic shut off when cartridges are removed with a simple, 1/4 turn.



No filter or membrane housings!

- No mess!
- No fuss!

No need to disconnect tubing when replacing membranes.

Cartridges have double o-rings so they will not leak.

Quick connect fittings for easy installation.

## Options



### RO PRO® Storage tanks

Will not chip, rust or dent. Only 9" wide. Takes less space below the sink!



Metal Tank



Designer, top mount chrome faucet.



Long reach chrome faucet.

## Limited warranty

Systems come with a limited warranty covering defects in material and workmanship, extended to the original purchaser for one year from date of installation. See warranty for more details.